



Completely pre-assembled pump module is ready to install. All that is required is a standard electric duplex outlet and hose bibb for water supply. Simply plug in both electric and water and Quick Connect Mister supply line to pump outlet.

DIRECT DRIVE PUMPS

- Adjustable up to 1000 PSI
- All Stainless Steel Brass components
- Washdown duty motor with triplex plunger pump head
- Nylon pump base with 5 vibration isolators
- Solenoid water shut-off valve
- Glycerin filled pressure gauge

TECHNICAL SPECIFICATIONS

MODEL NUMBER	HP	Max # of Jets Gallons per Hour	VOLTS	AMPS	WATTS	WEIGHT	STANDARD DIMENSIONS
PM 1/3DD115 PM 1/3DD230	1/3	25	115 230	6.4 3.2	736	43.4 lbs 19.73 kg	<p>Same for All Models 21" L x 12" W x 10" H 53.5 cm x 30.5 cm x 25.4 cm</p>
PM 1/2DD115 PM 1/2DD230	1/2	36	115 230	8.8 4.4	1012	45.4 lbs 20.64 kg	
PM3/4DD115 PM3/4DD230	3/4	50	115 230	10.8 5.4	1242	49.2 lbs 22.36 kg	
PM1DD115 PM1DD230	1	65	115 230	12.8 6.4	1572	52.6 lbs 23.9 kg	
PM1.5DD115 PM1.5DD230	1 1/2	80	115 230	19 9.5	2185	56.3 lbs 25.6 kg	